



- \_\_\_\_\_ Slate
- \_\_\_\_\_ Batten and Counter Batten
- \_\_\_\_\_ Breather Membrane
- \_\_\_\_\_ Insulation - Mineral Wool
- \_\_\_\_\_ Insulation - Mineral Wool
- \_\_\_\_\_ Vapour Barrier
- \_\_\_\_\_ Internal Finish

1. Mounting profile
2. Integrated Thermal Collar
3. Double Trimmer (where necessary)

- \_\_\_\_\_ Slate
- \_\_\_\_\_ Batten and Counter Batten
- \_\_\_\_\_ Ventilation Path
- \_\_\_\_\_ Breather Membrane
- \_\_\_\_\_ Insulation - Mineral Wool
- \_\_\_\_\_ Insulation - Mineral Wool
- \_\_\_\_\_ Vapour Barrier
- \_\_\_\_\_ Internal Finish

|  |        |   |             |               |         |             |             |        |
|--|--------|---|-------------|---------------|---------|-------------|-------------|--------|
| www.keyliteofwindows.com<br>E-Mail: info@keylite.co.uk<br>Tel: 028 8675 8921 Fax: 028 8675 6923<br>Keylite Roof Windows Ltd, Cookstown,<br>County Tyrone, Northern Ireland BT18 8LU. |        | This drawing is for information and illustrative purposes only<br>and as such cannot constitute a basis for performance. All<br>Roof constructions needs to be sign with current building regulations.<br>Keylite is not responsible for any installation quality on the roof.<br>Documentation only. If printed for copying and posting, photocopying is prohibited. |             |               |         |             |             |        |
| Roofing Style  | Window | Flashing  | Felt Collar | Vapour Collar | Angle   | DWG No.     | Scale       | Format |
| max<br>min   | FE/TH  | SRF   | FC          | VC            | 15°-75° | FE/TH-SRF-1 | 1:5<br>1:10 | A3     |
|  |        |   |             |               |         | Rev. A 2018 |             |        |

