



- Ceramic Tile
- Batten and Counter Batten
- Breather Membrane
- Insulation - Mineral Wool
- Vapour Barrier
- Internal Finish

1. Mounting profile
2. Integrated Thermal Collar
3. Double Trimmer (where necessary)

- Ceramic Tile
- Batten and Counter Batten
- Ventilation Path
- Breather Membrane
- Insulation - Mineral Wool
- Vapour Barrier
- Internal Finish

4. Side Flashing Holding Piece

www.keyliteofwindows.com E-Mail: info@keylite.co.uk Tel: 028 8675 8921 Fax: 028 8675 8923 Keylite Roof Windows Ltd, Cookstown, County Tyrone, Northern Ireland BT80 8LU.		This drawing is for information and illustrative purposes only and as such cannot substitute a trade for performance. All materials and components used in this drawing are subject to change without notice. Roof constructions must be in line with current building regulations. Keylite is not responsible for any installation quality on the roof. Documentation only. If printed for copying and posting, photocopying is prohibited.	Roofing Style 	Window RWF	Flashing TRF-FS	Felt Collar FC	Vapour Collar VC	Angle 20°-90°	DWG No. RWF-TRF-FS Rev. A 2018	Scale 1:5 1:10	Format A3
--	--	--	-------------------	---------------	--------------------	-------------------	---------------------	----------------------	--------------------------------------	----------------------	--------------

