


Sun Guard GlazingGlazing

Keylite's solar control, Argon gas filled double glazing with self-cleaning coating and Low E coating lets the maximum light into the home while blocking 80% of external heat, preventing its transfer through the glass into your home, providing year round comfort.



Technical Information

Glazing Results			Sun Guard [SG]
UV	Transmittance	auuv	0.01
Thermal Performance	Thermal Conductance (U-Value) [W/(m².K)]	Ug	1.00
Light	Transmittance for standard illuminant D65	τν	0.50
	Reflectance for standard illuminant D65 (*) external	$ ho_{V}$	0.11
	For standard illuminant D65 (**) internal	ρν	0.13
	General colour rendering index	Ra	0.92
Energy	Solar direct transmittance	τe	0.22
	Solar direct reflectance (*) external	hoe	0.40
	Solar direct reflectance (**) internal	hoe	0.43
	Solar direct absorption (*)	a	0.36
	Secondary internal heat transfer factor (*)	qi	0.03
	Solar heat gain coefficient (SHGC)	g	0.24
	Shading coefficient (+g_DIN/0,87)(*)	SC	0.32
Sound	Sound reduction (dB)	rw	36

Glazing Make-Up

- ▶ Self-cleaning glass on outer pane.
- ▶ 4mm toughened outer pane.
- ▶ Sun Guard protective filter.
- ▶ 18mm Argon gas filled cavity.
- ▶ 6.38mm laminated inner pane.
- ▶ Ideal safety glazing for windows below 800mm from finish floor level or windows above head height.
- Improves sound reduction, safety and a reduction in the harmful effects of UV light. Warm edge glazing unit.



Keylite Australian Distribution

New South Wales

Natural Lighting Products Sydney Sales Office Unit 15, 2-8 South Street Rydalmere NSW 2116

Customer Service: 1300 859 561

Queensland

Natural Lighting Products Brisbane Sales Office Unit 18, 12-18 Ellerslie Road Meadowbrook Qld 4131

Email:

info@naturallighting.com.au

Victoria

Natural Lighting Products Victorian Sales Office Unit 13, 556-598 Princes Highway Noble Park Vic 3174

ACT

Natural Lighting Products Canberra Sales Office Unit 7, 87 Collie Street Fyshwick ACT 2609