

## Keylite Sunlite Specification

**MANUFACTURER:** Keylite Roof Windows  
Derryloran Industrial Estate  
Cookstown  
Co. Tyrone  
BT80 9LU

TELEPHONE ++44 (0)28 867 58921  
FAX ++44 (0)28 867 58923  
E-MAIL [info@keylite.co.uk](mailto:info@keylite.co.uk)

### Product Reference:

#### **KEYLITE Sunlite Rigid System: (SLRS)**

Sunlite Rigid Tubular Daylight System, designed for roof pitches between 15-60°. System complete with 2m of tubing and an integrated flashing kit. Additional extensions are available if required. System to be installed in accordance with manufacturers recommendations and not to exceed 4m in length.

#### **KEYLITE Sunlite Flexi System: (SLFS)**

Sunlite Flexible Tubular Daylight System, designed for roof pitches between 15-60°. System complete with 2m of tubing and an integrated flashing kit. System to be installed in accordance with manufacturers recommendations and not to exceed 2m in length.

### Size:

250mm diameter

350mm diameter

450mm diameter

530mm diameter

### Glazing Details:

4mm toughened outer glazing pane & double glazed acrylic ceiling diffuser with white ceiling trim.

## **Flashing to suit:**

Propriety (Enter appropriate flashing code from list below) Integrated Flashing Kit by Sunlite manufacturer to suit (Enter make & model of roofing finish).

**SRF:** Suitable for installation in slate and flat roofing materials, with a profile not exceeding 10mm thick. Not suitable with interlocking slate.

**TRF:** Suitable for installation in flat and profiled roofing materials, with a profile not exceeding 45mm thick. Not suitable with interlocking slate or profiled sheeting.

**FRF:** Suitable for installation in flat roofs when combined with the Sunlite Flat Roof System Up stand. Not suitable for installation with the Sunlite Flexi System.

## **Accessories:**

### **Rigid Extension: (SLRE)**

Additional 600mm long, single rigid extension piece to be fitted to Rigid System above.

**Note: Rigid Extension can ONLY be fitted to SLRS.**

### **Fluorescent Lamp: (SLL)**

Sunlite circular fluorescent lamp to be fitted to above Sunlite.

### **Fire Collar: (SLFC)**

Additional Sunlite 30 minute fire resistant collar. To be fitted to above Sunlite, directly above the ceiling diffuser.

### **Security Collar: (SLSC)**

Additional Sunlite security collar. To be fitted to above Sunlite, directly above the ceiling diffuser.